



GM003 - 1/4" Oval Gear Pulse Meter



The GM003 is another of the GPI compact pulse meters. This 1/4" Pulse Meter has an increased flow range and offers the same ability to handle a wide range of fluid viscosities with exceptional levels of repeatability.

ACCURACY: ± 1.0% OF READING

Select Your Body Material:

- Aluminum
- PPS
- Stainless Steel
- High Pressure Stainless Steel
- Intermediate Pressure Stainless Steel



Features and Benefits:

- ✓ Up to 1,000 cps viscosity with standard rotor; 1,000,000 high viscosity rotor.
- ✓ Compact size and extremely accurate even with viscous fluids.
- ✓ High viscosity stainless steel rotor available.
- ✓ Meter design minimizes the number of wear-able parts – extending product life.
- ✓ Handles particles sizes to 0.005"/0.127 mm.
- ✓ Comes with Reed Switch as standard, Hall Effect Sensor* optional.
- ✓ Choose from a variety of Output and Display Options.
- ✓ Certificate of Accuracy supplied with meter.

GM003 - SPECIFICATIONS

Fitting Type:	BSP or NPT (Female)
Sensor Options:	Reed Switch or Hall Effect Sensor*
Rotor Materials:	PPS, 316 Stainless Steel or High Viscosity SS
O-Ring:	Fluorocarbon (Std.), Perfluoroelastomer (Optional)
Output Options:	
Aluminum:	Pulse Out or Local 4-20 mA Transmitter
PPS:	Pulse Out or Local 4-20 mA Transmitter
Stainless Steel:	Pulse Out or Local 4-20 mA Transmitter
High Pressure SS:	Pulse Out
Intermed. Pressure SS:	Pulse Out or Local 4-20 mA Transmitter
Display Options:	Local Display or Local Display w/4-20 mA Output
Flow Range:	4 - 132 GPH (15 - 500 LPH)
Flow Range @ < 5 cps:	6 - 132 GPH (25 - 500 LPH)
Accuracy:	± 1.0% of reading
Repeatability:	± 0.03%
Maximum Viscosity:	Standard Rotors: 1,000 cps High Viscosity Rotors: 1,000,000 cps
Pressure Rating:	
Aluminum:	75 PSI / 5 BAR
PPS:	75 PSI / 5 BAR
Stainless Steel:	150 PSI / 10 BAR
High Pressure SS:	8000 PSI / 544 BAR
Intermed. Pressure SS:	800 PSI / 55 BAR
Maximum Temperature:	
Aluminum:	176°F / 80°C
PPS:	176°F / 80°C
Stainless Steel:	248°F / 120°C
High Pressure SS:	248°F / 120°C
Intermed. Pressure SS:	248°F / 120°C
Typical K-Factor:	1514.2 PPG / 400 PPL
Wetted Mat'l. - Housing:	
Aluminum:	Aluminum with PPS Cap
PPS:	PPS
Stainless Steel:	316 Stainless Steel
High Pressure SS:	316 Stainless Steel
Intermed. Pressure SS:	316 Stainless Steel
Wetted Mat'l. - Bearings:	
Aluminum:	Bronze
PPS Rotor:	N/A
Stainless Steel:	Ceramic
High Pressure SS:	Ceramic
Intermed. Pressure SS:	Ceramic
Wetted Mat'l. - Shaft:	
Aluminum:	316 Stainless Steel
PPS:	Hastalloy C / Stainless Steel
Stainless Steel:	316 Stainless Steel
High Pressure SS:	316 Stainless Steel
Intermed. Pressure SS:	316 Stainless Steel
Frequency Range:	1.7 - 55.5 Hz @ 4 - 132 GPH
Recommended Strainer Size:	200 mesh
Shipping Weight (approx.):	Aluminum/PPS = 1 lb. (0.45 kg), High Pressure Stainless Steel = 8 lbs. (3.63 kg), SS/Intermediate Pressure SS = 2 lbs. (0.91 kg)
Remote Display:	Option Available: Model GG500
Remote Transmitter:	Options Available: Model GA500 & GX500

* Hall Effect Sensor requires dedicated power source.

BUY SMART . BUY VALUE . BUY